

# SUPPORT ACCESSORIES CASTERS

CASTER	CODE/CAPACITY PER PAIR	CASTER	CODE/CAPACITY PER PAIR
4" DIA. RUBBER RIGID	4RR/600 LBS.	4" DIA. RUBBER SWIVEL W/ BRAKE	4RSB/-
4" DIA. STEEL RIGID	4SR/700 LBS.	6" DIA. RUBBER RIGID	6RR/1120 LBS.
4" DIA. V-GROOVE RIGID	4VR/-	6" DIA. STEEL RIGID	6SR/1150 LBS.
4" DIA. RUBBER SWIVEL	4RS/600 LBS.	6" DIA. RUBBER SWIVEL	6RS/1120 LBS.
4" DIA. STEEL SWIVEL	4SS/700 LBS.	6" DIA. STEEL SWIVEL	6SS/1150 LBS.
4" DIA. V-GROOVE SWIVEL	4VS/-	6" DIA. STEEL SWIVEL W/ BRAKE	6SSB/-
FLOORLOCK FOR 4" CASTER	-	FLOORLOCK FOR 6" CASTER	-

## SPECIFICATIONS

**CASTERS:** 4" dia. or 6" dia., steel or rubber, swivel or rigid, V-groove casters; floor locks, wheel brakes available. Two casters supplied per support with enlarged mounting plate welded to legs.

**CAPACITY:** Up to 1150 lb. caster capacity. Consult factory for heavy duty casters.

**OPTIONAL:** Angle track for V-groove.



## CASTERS FOR LIGHT DUTY CONVEYORS

### SLC-5-16-4SRBF

SLC-(elevation code)-(between frames\*)-(caster model\*\*)-(floorlock@)

\*Specify 10", 16" or 22" between frames only. Model SLC is suited specifically for wheel conveyors and 138 gravity series.

\*\*See chart for caster model number.

@Specify F if floorlock required.

## CASTERS FOR MEDIUM DUTY CONVEYORS

### SMC-4-13-4RSBF

S (medium or heavy duty\*) C-(elevation code)-(between frames)-(caster model\*\*)-(floorlock@)

\*Specify M for medium duty supports and H for heavy duty supports.

\*\*See chart for caster model number.

@Specify F if floorlock required.

■ 2 week shipment

# KNEE BRACE AND ADJUSTABLE SUPPORT BRACKET

MEDIUM DUTY KNEE BRACE MODEL KB CODE NO.	HEAVY DUTY KNEE BRACE MODEL HKB CODE NO.	POLYTIER KNEE BRACE MODEL PKB CODE NO.	NOSE-OVER KNEE BRACE MODEL NOKB CODE NO.
2	2	-	6
4	4	4	-
6	6	6	-
8	8	8	-
10	10	10	-
12	12	-	-
-	14	-	-

## SPECIFY KNEE BRACE MODEL NUMBER

### KB-6

(model number\*)-(code number)

\*Specify KB (medium duty for SL or SM supports), HKB (heavy duty for SH or SS supports), PKB (for polytier supports) or NOKB (for mounting on nose-over).

## ADJUSTABLE SUPPORT BRACKET C-3

### C-3

C-3

## SPECIFICATIONS

**KNEE BRACE:** Available in 3 styles; Model KB (10 ga.) for SL and SM supports, Model HKB (7 ga.) for SH and SS supports and Model PKB (10 ga.) for polytier supports.

**C-3 ADJUSTABLE SUPPORT BRACKET:** 10 ga. construction on support Models SL and SM; 7 ga. on Model SH.



KB knee braces add strength to permanent supports and stability in portable applications. C-3 adjustable support bracket allows support to be attached easily to conveyor.



■ 24 hour shipment

